

tesa® Professional 4668 Transparent PE Tape

Product Information

Transparent duct tape

Product Description

tesa® 4668 is a polyethylene tape based on a transparent PE film and an acrylic adhesive. tesa® 4668 is a very strong tape for a wide range of applications, often used for splicing of LDPE films in constructions and house buildings.

Features:

- excellent UV resistance
- strong, ageing-resistant adhesive
- weather- and waterproof
- good abrasion resistance
- very good resistance to solvents

Product Features

- Indoor and outdoor applications
- Repairing of plastic materials
- Affixing LDPE films in construction applications
- Sealing of plastic bags
- Transparent film for nearly invisible repairs

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------|-------------------|--------|
| • Backing | PE film | • Total thickness | 140 µm |
| • Type of adhesive | acrylic | | |

Properties/Performance Values

- | | |
|--------------------|---------|
| • Tensile strength | 20 N/cm |
|--------------------|---------|

Certificates

Certified according to

- none

tesa[®] Professional 4668 Transparent PE Tape

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=4668PRO>